

NEW

YF-2G-N

MOTO FUEL



Tubo bicapa para carburantes en motos. Según normativa Japonesa YF-2G-N.



Tub bicapa per a carburants en motos. Segons normativa Japonesa YF-2G-N.

Tubo de duas camadas para combustível em motocicletas. De acordo com os regulamentos japoneses YF-2G-N.

Tuyau bicouches pour le carburant des motos. Selon la réglementation japonaise YF-2G-N.

Tubo bistrato per il carburante in moto. Secondo le normative giapponesi YF-2G-N.

Doppelschichtrohr für Kraftstoffe in Motorrädernach japanischen Vorschriften YF-2G-N.

Bilayer pipe for fuels in motorcycles. According to Japanese regulations YF-2G-N.



Material: NBR de alto contenido + CSM. **Propiedades:** Tubo resistente al ozono : 70 horas a 100°C - 50 ppm. Resistente a la llama.
Material: high content NBR + CSM. **Properties:** Ozone resistant tube: 70 hours at 100°C - 50 ppm. Flame resistant.
Matériel: NBR à haute teneur + CSM. **Propriétés:** Tube résistant à l'ozone: 70 heures à 100°C - 50 ppm. Résistant aux flammes.
Material: Hoher Gehalt NBR + CSM. **Eigenschaften:** Ozonbeständiges Rohr: 70 Stunden bei 100 °C - 50 ppm. Flammwidrig.
Material: NBR d'alt contingut + CSM. **Propietats:** Tub resistant a l'ozó: 70 hores a 100°C - 50 ppm. Resistente a la flama

Datos técnicos

| Referencia Referència Référence Riferimento Best.-Nr. | Diámetros Diâmetros Diamètres Diometri Durchmesser | | Formato Format Format Format Format | | Peso aproximado Peso aproximado Poids approximatif Peso approssimativo Ungefähres Gewicht | |
|---|--|---|---|---|---|---|
| | Interior Interior Intérieur Interni Innen | Exterior Exterior Extérieur Esterno Außen | Kit Kit Kit Kit Kit | Bobina Coll Bobine Bobine Spule | | |
| | mm (") | mm | Mt | Mt | Kg/m | |
| TF4,5x9 | 4,5 (3/16) ± 0,15 | 9 ± 0,5 | 2 | 25 | 0,080 | ○ |
| TF6x10,5 | 6 (1/4) ± 0,15 | 10,5 ± 0,5 | 2 | 25 | 0,100 | ○ |

