

TN



Tubo flexible para la limpieza con nitrógeno N² y gases inertes.



Tub flexible per a la neteja amb nitrogen N² i gasos inerts.

Tubo flexível para a limpeza com nitrogénio N² e gases inertes.

Tuyau flexible pour le nettoyage avec du nitrogène N² et des gaz inertes.

Tubo flessibile per la pulizia con azoto N² e gas inerti.

Förderschlauch für Reinigungsanlagen auf Stickstoff oder Inertgasbasis.

Hose suitable for nitrogene N².

D. RIBAS S.L. TUBO NITROGENO

TARGON



Manguera flexible para el transporte de argón.



Mànega flexible per al transport d'argó.

Mangueira flexível para o transporte de argón.

Tuyau flexible pour le transport d'argon.

Condotto flessibile per il trasporto di argon.



Argonschlauch.

Hose suitable for argon transport.

D. RIBAS, S.L. TARGON ISO 3821 20 BAR (2,0 Mpa)

Datos técnicos

Referencia Referència Référence Riferimento Best.-Nr.	Diámetros Diâmetros Diamètres Diametri Durchmesser		Presión Pressão Pression Pressione Druck		Radio curvatura mínimo Rádio curvatura mínimo Rayon courbure minimum Raggio di curvatura mínimo Biegeradius Min.-Wert		Peso aproximado Peso aproximado Poids approximatif Peso approssimativo Ungefähres Gewicht		
	Interior Intérieur Intérieur Interni Innen	Exterior Extérieur Esterno Außen	Trabajo Trabalho Travail Lavoro Arbeit	Rotura Rotura Rupture Rottura Bruch	Bar	Psi	Bar	Psi	r mm
TN - 12	12 ± 0,5 (1/2)	20 ± 0,2	20	290	60	870	80	0,264	△
TN - 19	19 ± 0,5 (3/4)	29,5 ± 0,2	20	29	60	870	150	0,487	△
TARGON - 06	6 ± 0,5 (1/4)	13 ± 0,2	20	290	60	870	35	0,174	□
TARGON - 08	8 ± 0,5 (5/16)	15 ± 0,2	20	290	60	870	45	0,168	□
TARGON - 19	19 ± 0,5 (3/4)	29,5 ± 0,2	20	290	60	870	220	0,490	○



○ En Stock □ Ocasionalmente en Stock △ Bajo demanda