

NEW

FKM HOSE



Manguera para transporte de ácidos, aromáticos, líquidos petroquímicos, etc.



Mànega per al transport d'àcids, aromàtics, líquids petroquímics.

Mangueira para o transporte de ácidos aromáticos, líquidos petroquímicos.

Tuyau pour le transport des acides, des aromatiques, des liquides pétrochimiques, etc.

Tubo per il trasporto di acidi, liquidi aromatici e petrolchimici.

Schlauch für den Transport von Säuren, aromatischen, petrochemischen Flüssigkeiten.

Hose suitable for the handling of chemicals.



Applications: Aggressive chemical and solvent transfer. Not intended for use with steam. Laboratory hose, peristaltic pump.

Key Features:

- Temperature: -40°C up to +225°C.
- Excellent resistance to fuels, oils, lubricants, high temperatures, hydrocarbons and most mineral acids.
- Low permeation to fuels and gases
- -40°C to +225°C service temperature range
- Resistant to all fuels / fuel mixtures
- Resistant to 'sour' fuel
- Resistant to oils
- High strength to resist damage

Datos técnicos

Referencia Referència Référénto Riferimento Best.-Nr.	Diàmetros Diámetros Diamètres Diametri Durchmesser		Grosor de pared Gruix paret Épaisseur de paroi Spessore della parete Wandstärke		Longitud rollo Longitud rull Longueur de bobine Lunghezza Spulenlänge		Peso aproximado Pes aproximad Peso approssimativo Poids approximatif Ungefähres Gewicht		MOQ Quantitat mínima Quantité minimum Quantità minima Mindestbestellmenge	
	Interior Interior Intérieur Interni Innen	Exterior Exterior Extérieur Esterno Außen								
	mm (")	mm	mm	mm	m	Kg/m		m		
FKM HOSE - 03	3 (1/8)	7	2	2	50-55	0,051	△	200		
FKM HOSE - 04	4 (5/32)	8	2	2	50-55	0,062	△	200		
FKM HOSE - 05	5 (13/64)	8	1,5	1,5	50-55	0,059	△	200		
FKM HOSE - 06	6 (1/4)	9	1,5	1,5	50-55	0,067	△	150		
FKM HOSE - 07	7 (9/32)	10	1,5	1,5	50-55	0,076	△	150		
FKM HOSE - 08	8 (5/16)	11	1,5	1,5	50-55	0,099	△	100		
FKM HOSE - 09	9 (23/64)	12	1,5	1,5	50-55	0,095	△	100		
FKM HOSE - 10	10 (3/8)	13	1,5	1,5	50-55	0,102	△	100		

